



ATC700

Mini asset tracker

Quick Manual v1.3 | 2026-05-21



CONTENTS

Glossary	3	Mounting recommendations	11
Safety information	4	Troubleshooting	12
Know your device	6	LED indications	12
Set up your device	7	Basic characteristics	13
PC connection (Windows)	8	Certification and approvals	15
How to install USB drivers (Windows)	8	Warranty	16
Configuration (Windows)	8	Company details	17



GLOSSARY

CEP – Circular Error Probable: a statistical measure used to describe the accuracy of a positioning system, commonly used in the context of GNSS. CEP represents the radius of a circle, centered on the true position, within which a given percentage (usually 50%) of the measured positions are expected to fall.

COM port – Serial communication interface that is used to transfer information to/from devices such as modems, terminals and various peripherals.

COLD start – A COLD start occurs when the GNSS receiver lacks all the necessary information for a position fix, requiring it to start from scratch. This means it needs to acquire and decode the almanac and ephemeris data from the satellites, determine the satellite positions, and calculate its position.

FOTA – Firmware-Over-The-Air.

HOT start – A HOT start occurs when the GNSS receiver has all the necessary information to calculate a position fix readily available. This includes the almanac and ephemeris data, the approximate time, and its last known position.

IMEI – International Mobile Equipment Identity: a unique numeric identifier used by networks to identify devices.

NITZ – Network Identity and Time Zone: a mechanism in GSM, used to provision time, date and other parameters to mobile devices in a network.

NTP – Network Time Protocol: a networking protocol for clock synchronization between computer systems.

SELV – Safety Extra Low Voltage: an electrical system in which the voltage cannot exceed 50 VAC or 120 VDC under normal conditions, and under single-fault conditions, including earth faults in other circuits.

Record – AVL data stored in device memory. AVL data contains GNSS and I/O information.

WARM start – A WARM start occurs when the GNSS receiver has some, but not all, of the necessary information for a position fix. It might have valid almanac data but needs to download new ephemeris data or doesn't have an accurate estimate of its current time or position.

i SIM card should be inserted in the module while the connector is plugged off (while module has no power).



SAFETY INFORMATION

This section contains information on how to operate ATC700 safely. By following these requirements and recommendations, you will avoid dangerous situations. You must read these instructions carefully before operating the device and follow them strictly!

To avoid mechanical damage, it is advised to transport the device in an impact-proof package. Before usage, the device should be placed so that its LED indicators are visible. They show the status of device operation.

SIGNALS AND SYMBOLS

Warnings and cautions which are general to the use of the device under all circumstances are included in this section. Some warnings and cautions are also inserted within the manual where they are most meaningful.



CAUTION! Cautions alert users to exercise appropriate care for safe and effective use of the product.



WARNING! This classifies a hazard of medium risk level. Failure to comply with the warning may result in serious injury.



Please note: Notes provide additional guidelines or information.



WARNING: Do not disassemble the device. If the device is damaged, the power supply cables are not isolated or the isolation is damaged, **DO NOT** touch the device before unplugging the power supply.



All wireless data transferring devices produce interference that may affect other devices which are placed nearby.



The device must be connected only by qualified personnel.



The device must be firmly fastened in a predefined location.



The programming must be performed using a PC with autonomic power supply.



Installation and/or handling during a lightning storm is prohibited.



The device is susceptible to water and humidity.



WARNING: Risk of explosion if battery is replaced by an incorrect type. Dispose of used batteries according to the instructions.



Battery should not be disposed of with general household waste. Bring damaged or worn-out batteries to your local recycling center or dispose them to battery recycle bin found in stores.



This sign on the package means that all used electronic and electric equipment should not be mixed with general household waste.

DATA SAFETY AND PRIVACY

In accordance with the General Data Protection Regulation (GDPR), this Data Processing Agreement (DPA) establishes obligations between Teltonika, the data processor, and its customers, acting as data controllers. The DPA outlines how Teltonika will handle customer data while adhering to GDPR regulations. This includes details on the data Teltonika can process, security measures in place, and customer rights concerning their data.


For a comprehensive understanding of the agreement, including permitted sub-processors, data breach procedures, and dispute resolution, please refer to the full Data Processing Agreement:

teltonika-gps.com/about-us/policies-certificates/data-processing-agreement




KNOW YOUR DEVICE

Top view




1. Status RGB LED
2. Configurable button
3. USB Type-C connector

Top view (without cover)



4. GNSS antenna
5. SIM slot
6. LTE antenna

Bottom view (without cover)




7. Battery connector
8. Modem

STANDARD PACKAGE CONTAINS

- 1 pc. ATC700 tracker
- 1 pc. USB-C cable
- 1 pc. USB-C Dust plug
- Packaging box with Teltonika branding




SET UP YOUR DEVICE



1. Remove top cover (1)


You will receive the tracker with the top cover partially closed. Use a pry tool¹ and open one side of the top cover.

Warning: When opening the cover, avoid touching the USB port to prevent its small rubber seal from coming off.




2. Remove top cover (2)

Turn the device. Use a pry tool¹ and open the other side of top cover. Gently remove top cover.




3. Insert SIM card

Insert SIM card as shown. Make sure Nano-SIM card cut-off corner is pointing towards SIM slot.



4. Re-attach top cover

Ensure that both sides are fully secured and a clicking sound is heard when closing.



5. Device is ready

Device is ready to be mounted.

¹ The pry tool is not included



PC CONNECTION (WINDOWS)

1. Connect device to the computer using USB Type-C cable.
2. Install USB driver, see “How to install USB drivers (Windows)”

HOW TO INSTALL USB DRIVERS (WINDOWS)

1. Download COM port drivers from [here](#)¹.
2. Extract and run **TeltonikaCOMDriver.exe**.
3. Click **Next** in driver installation window.
4. In the following window click **Install** button.
5. Setup will continue installing the driver and eventually the confirmation window will appear. Click **Finish** to complete the setup.

CONFIGURATION (WINDOWS)

Most Teltonika devices are shipped with default factory settings. Use [Telematics Configuration Tool \(TCT\)](#)² to change these settings according to your needs.

TCT	
Operating system	Windows 10 Windows 11
MS .NET Framework version	MS .NET framework 6.0
Version	64 bit
Disk Storage	1 GB of free disk space
Internet	Ethernet port or Wi-Fi w/ network access for auto-update


¹ wiki.teltonika-gps.com/images/d/d0/TeltonikaCOMDriver.zip

² wiki.teltonika-gps.com/view/Getting_started_with_TCT



TCT

1. Download the TCT (compressed archive).
2. Extract the archive and launch the executable. The TCT will be installed.
3. Launch the TCT.
4. In the Discovered devices list, select your device and press **Configure**.
5. The Device status window opens. It contains device, GNSS, and Cellular information. Most important configurator sections are Mobile network (server, Mobile network settings) and Tracking settings (data collection parameters). More details about ATC700 configuration using TCT can be found on our [Wiki](#)³.



Save to device

Save to device – saves configuration to device.

Upload file (.cfg)

Upload file – loads configuration from file.

Save to file

Save to file – saves configuration to file.

Update

Update – update device firmware.

Reset configuration

Reset configuration – sets device configuration to default.

DEFAULT CONFIGURATION SETTINGS

RECORDS SENDING TO SERVER:

A record with location will be transmitted to the server **every 15 minutes**, regardless of the product's movement status.

SLEEP MODE:

The device is configured with **Power Off Sleep** mode enabled by default to ensure maximum operating time.

The device will not send any records until the server parameters (Domain, and port) are configured. During this time, all records are stored in the device's internal memory. Once configured, the stored data is automatically transmitted to the specified server.

Time intervals and default I/O elements can be changed by using TCT⁴, SMS parameters⁵ or FOTA Web.

⁴ https://wiki.teltonika-gps.com/view/ATC700_Configuration

⁵ https://wiki.teltonika-gps.com/view/ATC700_Parameter_List

³ wiki.teltonika-gps.com/view/ATC700_Configuration



QUICK SMS CONFIGURATION

The default configuration ensures best track quality and optimal data usage.

Quickly set up your device by sending this SMS command to it:

```
« setparam 2001:APN;2002:APN_username;2003:APN_password;2004:Domain;2005:Port;2006:0»
```

1

2

3

4

5

6

7


- 1 Before SMS text, one space symbol should be inserted. This space is dedicated to device SMS password.

GPRS SETTINGS:

- 2 **2001** – APN
- 3 **2002** – APN username (leave field empty if there is no APN username)
- 4 **2003** – APN password (if there are no APN password, empty field should be left)


SERVER SETTINGS:

- 5 **2004** – Domain
- 6 **2005** – Port
- 7 **2006** – Data sending protocol (0 – TCP, 1 – UDP)






MOUNTING RECOMMENDATIONS




1. ZIP TIE

Quick and secure attachment for various surfaces, ideal for permanent installation.




2. DOUBLE-SIDED TAPE¹

Easy and fast mounting on flat surfaces without any tools.



3. MAGNETIC STICKER¹

Flexible solution for quick attachment and removal on metal surfaces.



4. THIN CORD

Convenient for carrying — can be worn around the neck or attached as needed.

¹ This accessory can be included in the product package. Please contact your sales representative to arrange this.



TROUBLESHOOTING

Troubleshooting section provides guidance to resolve frequently encountered issues during the setup and operational phases of the ATC700 device.

FREQUENTLY USED SMS/GPRS COMMANDS

Command	Description	Response sent on success?	Response sent on failure?
cpureset	Restarts the device	No	Yes
getstatus	Returns status of the device	Yes	Yes
allver	Returns information about device firmware and hardware	Yes	No
web_connect	Triggers FOTA service / connection	Yes	Yes

LED INDICATIONS¹

Meaning	Colour	Behaviour	Duration
Power on	Green	Steady	3 s
Low Battery	Red	Blinking - 1 s ON / 1 s OFF	Until power off
Charging	Yellow	Pulsing - fade in 2 s / fade out 2 s	Until charged or USB disconnected

100% charged	Green	Steady	Until USB disconnected
FW update	Blue	Blinking - 0.1 s ON / 0.1 s OFF	Until update finished
CFG uploading	Blue	Steady	3 s
Periodic record sending	Yellow	Blinking - 0.2 s ON / 2 s OFF	Until record is sent or failed
Record sent with GNSS fix	Blue	Steady	3 s
Record sent no GNSS fix	Yellow	Steady	3 s
Record sending failed	Red	Steady	3 s
Alarm	Red	Pulsing - 0.5 s fade in / 0.5 s fade out	6 s
Normal operation	Blue	Blinking - 0.5 s ON / 1 min OFF	In idle
Power OFF	Red	Steady	2 s

¹ This feature will not be available in the pilot batch.



BASIC CHARACTERISTICS

Module

Name	ATC700-QJAE0: Quectel EG915U-EU with AG3335 ATC700-QKAE0: Quectel EG915U-LA with AG3335
Technology	LTE CAT 1/GSM/GPRS/GNSS

GNSS

GNSS GPS, GLONASS, GALILEO, BEIDOU

Receiver L1: 75 channel

Tracking sensitivity -165 dBm

Position Accuracy < 1.8 m CEP

Velocity Accuracy < 0.1 m/s (within +/- 15% error)

Hot start < 1 s

Warm start < 25 s

Cellular

2G bands **ATC700-QJAE0:** GSM: B2/B3/B5/B8
ATC700-QKAE0: GSM: B2/B3/B5/B8

4G bands **ATC700-QJAE0:** LTE FDD: B1/B3/B5/B7/B8/B20/B28
ATC700-QKAE0: LTE FDD: B2/B3/B4/B5/B7/B8/B28/B66

Data transfer LTE FDD (CAT 1): Max. 10 Mbps (DL) / Max. 5 Mbps (UL)
GSM (GPRS): Max. 85.6 Kbps (DL) / Max. 85.6 Kbps (UL)

Transmit power Class 4 for GSM850/900: 33±4dBm
Class 1 for GSM1800/1900: 30±2dBm
Class 3 for LTE-FDD: 23±2dBm

Data support SMS (TEXT, PDU), Network protocols (TCP, UDP)

Power

Internal battery 1000 mAh Li-Po, 3.7V (3.7Wh)

Internal fuse 3A

Power Consumption Normal operation: 74.26 mA
Online Deep Sleep: 10.80 mA
Power Off Sleep: 0.11 mA

Interface

GNSS antenna Internal High Gain

GSM antenna Internal High Gain

USB 2.0 USB Type-C

LED indication 1 status RGB LED light

SIM Nano-SIM

Memory 128MB internal flash memory



Physical Specification

Dimensions 62.2 × 54.2 × 20.33 mm (L x W x H)

Weight 71 g

Operating Environment

Operating temperature (with battery) -20°C to +60°C

Battery charge temperature 0°C to +45°C

Storage temperature (with battery) -10 °C to +25 °C for 1 month
0 °C to +25 °C for longer than 3 months

Operating humidity 5% to 95% non-condensing

Ingress Protection Rating IP65 (internally tested, not certified). IP68 - in development.

Data Codec

Data sending protocols Codec 8 extended²

Features

Sensors Accelerometer

Scenarios Movement-based tracking, Periodic tracking, Scheduler, Alarm button, Power bank support, Configurable LED indication, Geofence², Geofence with time zone², On-demand tracking^{2 3}

Sleep modes Online Sleep, Power Off Sleep

Configuration and firmware update FOTA Web⁴, Teltonika Configurator (TCT)⁵

Time Synchronization GPS, NTP

Movement detection Accelerometer

² wiki.teltonika-gps.com/view/Codec#Codec_8_Extended

² Feature is still under development

³ wiki.teltonika-gps.com/view/ATC700_Features_settings

⁴ wiki.teltonika-gps.com/view/FOTA_WEB

⁵ https://wiki.teltonika-gps.com/view/Teltonika_Configurator



CERTIFICATION AND APPROVALS



This sign on the package means that it is necessary to read the User's Manual before your start using the device. Full User's Manual version can be found in our [Wiki](#)¹



This sign on the package means that all used electronic and electric equipment should not be mixed with general household waste.



Hereby, Teltonika declare under our sole responsibility that the above described product is in conformity with the relevant Community harmonization: European Directive 2014/53/EU (RED).



UK Conformity Assessed (UKCA) marking is a conformity mark that indicates conformity with the applicable requirements for above described products sold within Great Britain.



The Australian Standard AS/NZS 4417.1 and AS/NZS 4417.2 Marking of electrical products to indicate compliance with regulations – General rules for use of the mark provides general requirements for the use of the RCM including location of the marking on the equipment and its dimensional requirements.



E-Mark and e-Mark are the European conformity marks issued by the transport sector, indicating that the products comply with relevant laws and regulations or directives. Vehicles and related products need to go through the E-Mark certification process to be legally sold in Europe.

CHECK ALL CERTIFICATES

All newest certificates may be found in our [Wiki](#)²

¹ wiki.teltonika-gps.com/view/ATC700_Certification_%26_Approvals

² wiki.teltonika-gps.com/view/ATC700



WARRANTY

We guarantee our products 24-month warranty¹ period.

All batteries carry a 6-month warranty period.

Post-warranty repair service for products is not provided.

If a product stops operating within this specific warranty time, the product can be:

- Repaired
- Replaced with a new product
- Replaced with an equivalent repaired product fulfilling the same functionality
- Replaced with a different product fulfilling the same functionality in case of EOL for the original product

WARRANTY DISCLAIMER

Customers are only allowed to return products as a result of the product being defective, due to order assembly or manufacturing fault.

Products are intended to be used by personnel with training and experience.

Warranty does not cover defects or malfunctions caused by accidents, misuse, abuse, catastrophes, improper maintenance or inadequate installation – not following operating instructions (including failure to heed warnings) or use with equipment with which it is not intended to be used.

Warranty does not apply to any consequential damages.

Warranty is not applicable for supplementary product equipment (i. e. PSU, power cables, antennas) unless the accessory is defective on arrival.

[More information on what is RMA²](#)

¹Additional agreement for an extended warranty period can be agreed upon separately.

²wiki.teltonika-gps.com/view/RMA_guidelines



COMPANY DETAILS

Teltonika Telematics
Saltoniškių g. 9B,
LT-08105 Vilnius, Lithuania
Phone: +370 612 34567



TELEMATICS WEBSITE
teltonika-gps.com

For more information about our products and services, please visit our website: teltonika-gps.com.



WIKI KNOWLEDGE BASE
wiki.teltonika-gps.com

For technical assistance, troubleshooting, and further inquiries, refer to our comprehensive support resources at our technical assistance portal: [Teltonika Wiki](https://wiki.teltonika-gps.com).



FOTA WEB
fota.teltonika.lt